



US009636874B2

(12) **United States Patent**
Hatta et al.

(10) **Patent No.:** **US 9,636,874 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **HOOP WINDING DEVICE, FILAMENT WINDING APPARATUS AND MANUFACTURING METHOD OF TANK**

(71) Applicants: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota-shi, Aichi-ken (JP); **Murata Machinery, Ltd.**, Kyoto-shi, Kyoto (JP)

(72) Inventors: **Ken Hatta**, Okazaki (JP); **Daigoro Nakamura**, Kyoto (JP); **Motohiro Tanigawa**, Kyoto (JP); **Tadashi Uozumi**, Kyoto (JP)

(73) Assignees: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota-Shi (JP); **MURATA MACHINERY, LTD.**, Kyoto-Shi (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/437,026**

(22) PCT Filed: **Oct. 9, 2013**

(86) PCT No.: **PCT/JP2013/006005**

§ 371 (c)(1),

(2) Date: **Apr. 20, 2015**

(87) PCT Pub. No.: **WO2014/064895**

PCT Pub. Date: **May 1, 2014**

(65) **Prior Publication Data**

US 2015/0290882 A1 Oct. 15, 2015

(30) **Foreign Application Priority Data**

Oct. 23, 2012 (JP) 2012-233448

(51) **Int. Cl.**

B29C 70/16 (2006.01)

B29C 53/80 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **B29C 70/16** (2013.01); **B29C 53/8016** (2013.01); **B29C 71/02** (2013.01); **B29C 53/602** (2013.01); **B29L 2031/712** (2013.01)

(58) **Field of Classification Search**

CPC . B29L 2031/712; B29C 53/602; B29C 71/02; B29C 53/8016; B29C 70/16

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2009/0038759 A1 2/2009 Uozumi et al.
2009/0065622 A1* 3/2009 Uozumi B29C 53/70
242/410

FOREIGN PATENT DOCUMENTS

DE 8027362 U1 1/1981
DE 69818313 T2 6/2004

(Continued)

Primary Examiner — Jacob T Minskey

Assistant Examiner — Vishal I Patel

(74) *Attorney, Agent, or Firm* — Andrews Kurth Kenyon LLP

(57) **ABSTRACT**

There is provided a hoop winding device, comprising: a winding table configured to have an insertion hole formed to place a mandrel at a center thereof; a drive unit configured to rotate and drive the winding table; a plurality of supports on which bobbins with wound fibers are mounted, the plurality of supports being arranged along circumference of the winding table; a first guide section configured to bundle fibers drawn from a plurality of bobbins which constitute a first bobbin group out of the bobbins respectively mounted on the plurality of supports and feed the bundled fibers to the mandrel; and a second guide section configured to bundle fibers drawn from a plurality of bobbins which are not included in the first bobbin group but constitute a second bobbin group and feed the bundled fibers to the mandrel.

8 Claims, 9 Drawing Sheets

